

MULTIMATRIX
 / forceArc®
 / rootArc®
 / superPuls



- Networking of any number of different power sources via LAN/Wi-Fi by means of ewm Xnet software (option)
- Infinitely adjustable arc dynamics (choke effect)
- Large power reserves thanks to high duty cycle with all components heating up less as a result, guaranteeing a longer service life for machines when in use
- High-precision, powerful EWM eFeed 4-roll wire feed mechanism for secure feeding of all solid and flux cored wires
- Equipped for 1.2 mm steel wire
- Excellent torch cooling, resulting in cost savings on consumables due to high-performance centrifugal pump and 12-litre water tank
- Energy-saving thanks to high efficiency and standby function
- Multiprocess: MIG/MAG, TIG lift arc, MMA, air arc gouging
- Easy, tool-free change of welding polarity
- Synergic S: One-knob operation – easy setting of operating point, setting of all welding parameters and functions, and display of the welding parameters on the wire feeder, pre-programmed JOBs (welding tasks)
- High mains voltage tolerances +20%/-25% and therefore fully generator-compatible
- Ideally suited for use with long hose packages
- Connection capability for remote control and function torch
- Connection capability for MT function torches with X technology, without an additional control cable

	Taurus 401 Synergic S MM FDW					
	MIG/MAG		TIG		MMA	
Setting range for welding current	5 A - 400 A		5 A - 400 A		5 A - 400 A	
Duty cycle at ambient t.e	25 °C	40 °C	25 °C	40 °C	25 °C	40 °C
100 %	–	400 A	–	400 A	–	400 A
Open circuit voltage	80 V					
Mains frequency	50 Hz / 60 Hz					
Mains fuses (slow-blow)	3 x 32 A					
Mains voltage (tolerances)	3 x 400 V (-25 % - +20 %)					
Max. connected load	17.5 kVA		13.1 kVA		18.2 kVA	
Recommended generator power	25 kVA					
cos phi	0.99					
Efficiency	90 %					
Drive rolls	4					
Wire speed	Wire speed m/min, 0.5 m/min - 25 m/min					
Wire speed	Wire speed ipm, 19.68 ipm - 944.88 ipm					
Dimensions machine, LxWxH in mm	1100 x 455 x 1000					
Wire feeder, LxWxH in mm	660 x 280 x 380					
Weight, machine	118 kg					
Weight, wire feeder	13 kg					
Protection classification	IP 23					
Insulation class	H					
Standards	IEC 60 974-1; -10 / CE / S-Safety sign / EMC class A					